

Ocelot Drop-Arm Awning

Showroom
Unit 4 Kildare Close Eastcote Ruislip Middx
HA4 9LG 0208 866 6088
www.blindtechnique.co.uk

blind technique
Blinds Shutters Awnings



Technical Information

> Projection (mm)	750	1000	1250	1500
v Width (mm)				
1500	*	*	*	*
1750	*	*	*	*
2000	*	*	*	*
2250	*	*	*	*
2500	*	*	*	*
3000	*	*	*	*
3250	*	*	*	*
3500	*	*	*	*
3750	*	*	*	*
4000	*	*	*	*
4250	*	*	*	*
4500	*	*	*	*
4750	*	*	*	*
5000	*	*	*	*

- Width (mm): Up to 5000.
- Drop (mm): 750, 1000, 1250 and 1500.
- Standard RAL colour: White (9010).
- Corrosion resistant, powder coated, extruded aluminum framework.
- Stainless steel components for long lasting durability.
- Slim, flush cassette, ensuring that the fabric and components are protected from weather when retracted.
- Internal manual operation option available.
- TUV quality and CE safety marked.

155° Drop



90° Drop



Specification:

A drop-arm awning, available in sizes 1500mm - 5000mm in width x 750mm - 1500mm projection

Application:

Any domestic or commercial installation, but an ideal option for single story buildings.

Benefits:

Low cost, sturdy but lightweight. Subsequent sales for hotels, restaurants, cafe bars & pubs. The ultimate all weather awning.

The Ocelot is a **cost effective** way of shading. It is sturdy, but **lightweight**. Operating from a fixed pivot point, the Ocelot's projection and drop are the same. The **advantage** of these blinds is that they can be stopped in any position you require **ideal** for bungalows and single story extensions.



Top Das Icke, Ouberhausen.
Bottom Dr & Mrs Bell Alderley Edge.
Main Mr Coupes, Didsbury.